

**speco technologies™**

## Mini 3-Way Speaker System with Built in 70/25 Volt Transformer



### DMS-3TS

Features	Benefits
3-Way Polypropylene Speaker Construction	3 Cone drivers to capture full range of frequencies including crystal clear midrange
Aluminum Die-Cast Metal, Hermetically-Sealed Casing	Protects internal speaker components from exposure to the elements
Fine Mesh Aluminum Grille	Protects external speaker face from the elements and prevents rust
Multiple Wattage Settings	Allows individual wattage setting to application
Rotary Wattage Dial	Quick and easy wattage tap adjustments

### Specifications

Woofer	4" Air Suspension Polypropylene cone
Tweeter	1" Dome Tweeter
Midrange	2" Polypropylene Cone
Frequency Response	55Hz-20kHz
Power Rating	30 Watts RMS/ 50 Watts Max
Impedance	8 Ohms
Transformer	Built-in 70 and 25 Volt
Wattage Settings	15, 7.5, 4, 2, 1 Watts
Dimensions	7 3/8" H x 4 3/8" W x 4 1/8" D

Sold Individually, Available in White (DMS-3TSW)

#### Package Includes:

Removable mounting bracket	Speaker wire
Mounting Hardware	

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
 Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

DMS-3TS